九鼎新材料

通用型单向玻纤胶带

产品技术说明书

产品介绍:

JD4201A由玻璃纤维复合聚酯薄膜而成的通用单向纤维胶带。广泛用于工业捆扎、固定、托盘加固等应用。

特点:

- 耐撕裂。
- 对各种瓦楞纸板和实心板表面具 有出色的粘附力
- 具有良好的纵向抗拉强度、低伸 长率

用途:

- 捆扎
- 托盘加固
- 重型纸箱封口
- 货物运输固定
- 部件固定
- 钢卷封口固定

产品参数:

基材: PET+玻纤 粘结剂: 合成橡胶

颜色:透明

总厚度 (μm): 105

初粘: 12#

持粘: >24小时 粘结力: 25N/25mm 断裂强度: 600N/25mm

伸长率: ≤6%

联系方式:

地址: 江苏省如皋市中山东路1号

电话: 0513-80695629

邮箱: jdtape@jiudinggroup.com 网址: :www.jiudingtape.com



JD4506K

PET Battery Tape

Jiuding Tape

Technical Datasheet

Description:

Using double-layer polyester film as the base material, JD4506K tape features high tensile strength, excellent insulation properties, and resistance to punctures and scratches. The special adhesive formula ensures no residue is left on the adhered surface upon removal, meeting the requirements for fully automated production. The structural design with a backing film effectively reduces roll change time during the production process, minimizes labor hours in lithium battery manufacturing, and enhances


Application:

Specifically designed for wrapping the casing of power batteries and bundling battery packs, it provides insulation and protection for lithium batteries once charged. It is also suitable for areas of non-lithium battery products that require high levels of protection.

Specification:

Backing: PET Film Adhesive Type: Acrylic Total Thickness (µm): 110 Adhesion to Steel: 12N/25mm Breaking Strength: 150N/25mm

Die-electric:≥7000V Temp: up to 130°C



Plastic Liner Acrlic Adhesive PET Film Acrlic Adhesive

Contact:

Address: No.1 East Zhongshan Road, Rugao City, Jiangsu, China

Tel: 0086-513-80695629 E-mail: jdtape@jiudinggroup.com Web:www.jiudingtape.com

